

What is claimed is:

1. A portable image transfer system comprising:
 - a digital still camera, at a remote station, which captures images in digital form and stores the images in a camera memory;
 - a cellular telephone transmitter;
 - a central processing unit (CPU) coupled to the camera memory and the cellular telephone transmitter, wherein the CPU controls the camera memory to cause it to output data representing an image and the CPU controls the cellular telephone transmitter to cause a cellular telephone to transmit the data output from the camera memory;
 - a receiving station coupled to the cellular telephone transmitter by a cellular network to receive image data;
 - means, at the receiving station, for image processing;
 - means for resetting the camera memory to be reused for subsequent images once an image is transmitted to the receiving station;
 - a return link for sending commands from the receiving station to the CPU, wherein the commands are directions for obtaining further images as needed by the means for image processing; and
 - an image storage device coupled to the receiving station to store images received by the receiving station.
2. The apparatus of claim 1, wherein the CPU interfaces to a camera memory of an existing digital still camera.
3. The apparatus of claim 1, wherein the cellular telephone transmitter comprises:

6

- a standard cellular telephone; and
a cellular modem.
4. The apparatus of claim 1, further comprising means for
5 packaging images as electronic mail messages prior to
transmission by the cellular telephone transmitter.
5. The apparatus of claim 1, further comprising means for
handling a serial line interface protocol connection between
the cellular telephone transmitter and the receiving station.
- 10 6. The apparatus of claim 1, further comprising means for
encrypting image data prior to transmission by the cellular
telephone transmitter.
- 15 7. The apparatus of claim 1, further comprising a means
for causing the digital still camera to capture images on a
periodic basis, wherein the CPU is programmed to periodically
transmit an image to free the camera memory for
accepting subsequent images.
- 20 8. The apparatus of claim 1, further comprising means for
determining a location of the portable image transfer system
and means for including a location indication with each
image.
- 25 9. The apparatus of claim 1, wherein the commands
represent user directions to be displayed at the remote
station directing the user to capture additional images as
needed by the means for image processing.
- 30 10. The apparatus of claim 1, wherein the commands are
directions directed at the remote station directing the digital
still camera or CPU to capture additional image data as
needed by the means for image processing.
- 35 11. The apparatus of claim 1, further comprising a remote
printing device for printing images processed by the receiving
station.
- 40 12. The apparatus of claim 11, wherein the remote printing
device is one of a facsimile machine, a digital copier or
a printer.
13. The apparatus of claim 8, further comprising means,
within the receiving station, for using the location indication
as a variable when processing said each image.

* * * * *